

What is claimed is:

1. An accessory assembly for a vacuum cleaner comprising:  
an accessory body;  
a crevice attachment and an upholstery attachment both formed integrally with the  
5 accessory body; and  
a dusting attachment movably disposed on the accessory body.
2. The accessory assembly according to claim 1, wherein the accessory body, the  
crevice attachment and the upholstery attachment are integrally formed and are in fluid  
10 communication with each other.
3. The accessory assembly according to claim 1, wherein the dusting attachment is  
mounted around the outer surface of the accessory body and being slidably attached thereto.
- 15 4. The accessory assembly according to claim 1, wherein the crevice attachment  
and the upholstery attachment are integrally formed at opposite ends of the accessory body.
5. The accessory assembly according to claim 1, wherein the accessory body has a  
diameter, the crevice attachment has a suction port smaller than the diameter of the  
20 accessory body, the upholstery attachment has a widened section larger than the diameter of  
the accessory body, and the dusting attachment further comprises brush bristles having ends.
6. The accessory assembly according to claim 5, wherein the accessory body is  
formed with a longitudinal rail slot for slidably mounting and for guiding the dusting

attachment, and one side of an inner surface of the dusting attachment is formed with a rail projection having a size, configuration and orientation corresponding to the longitudinal rail slot.

5           7. The accessory assembly according to claim 6, wherein one end of the longitudinal rail slot is formed with a first locking projection for retaining the rail projection, the other end of the longitudinal rail slot is formed with a circumferential rail slot to accommodate retention of the dusting attachment when it is turned to a predetermined angle and fixed, and a second locking projection is formed in the circumferential rail.

10

8. The accessory assembly according to claim 7, wherein the brush bristles extend beyond the suction port of the crevice attachment when the dusting attachment is engaged to the second locking projection.

15           9. The accessory assembly according to claim 5, wherein the widened section of the upholstery attachment is provided with a floor brush that contacts the surface to be cleaned.

10           10. The accessory assembly according to claim 5, wherein the suction port of the crevice attachment has an inclined opening relative to the longitudinal direction of the accessory body, and the brush bristles are inclined in the same orientation as the opening of the suction port of the crevice attachment.

11. The accessory assembly according to claim 10, wherein the widened section of the upholstery attachment is formed to be symmetrically but oppositely inclined relative to

the incline orientation of the suction port of the crevice attachment when taken with reference to the longitudinal direction of the accessory body.